

# SMD Unshielded Power Inductors – SSL Series

## SSL Series


### Features

- RoHS, Halogen Free and REACH Compliance
- Unshielded power inductor
- Various package size and wide inductance range. SSL-HC family is designed for low resistance and high current purpose

### Applications

- DC/DC converters


### Product Identification



- Packaging: T : Tape and Reel , B : Bulk

### Shape and Dimensions


#### SSL0402



Dimensions in mm

| A                  | B                  | C                  | D    | E    | F    |
|--------------------|--------------------|--------------------|------|------|------|
| 6.60 <sup>+0</sup> | 4.45 <sup>+0</sup> | 2.92 <sup>+0</sup> | 1.02 | 1.27 | 4.32 |


### Recommended Pattern



Dimensions in mm


| TYPE    | A    | B    | C    | D    |
|---------|------|------|------|------|
| SSL0402 | 1.40 | 4.06 | 6.86 | 3.56 |

#### SSL0804/ 0810



Dimensions in mm


| TYPE    | A                   | B                  | C                   | D    | E    | F    |
|---------|---------------------|--------------------|---------------------|------|------|------|
| SSL0804 | 12.95 <sup>+0</sup> | 9.40 <sup>+0</sup> | 5.21 <sup>+0</sup>  | 2.54 | 2.54 | 7.62 |
| SSL0810 | 12.95 <sup>+0</sup> | 9.40 <sup>+0</sup> | 11.43 <sup>+0</sup> | 2.54 | 2.54 | 7.62 |



Dimension in mm


| TYPE    | A    | B    | C     | D    |
|---------|------|------|-------|------|
| SSL0804 | 2.92 | 7.37 | 13.21 | 2.79 |
| SSL0810 | 2.92 | 7.37 | 13.21 | 2.79 |

#### SSL1306



Dimensions in mm

| A                   | B                   | C                  | D    | E    | F    |
|---------------------|---------------------|--------------------|------|------|------|
| 18.54 <sup>+0</sup> | 15.24 <sup>+0</sup> | 7.11 <sup>+0</sup> | 2.54 | 2.54 | 12.7 |



Dimension in mm

| TYPE    | A    | B     | C     | D    |
|---------|------|-------|-------|------|
| SSL1306 | 2.92 | 12.45 | 18.29 | 2.79 |

# SMD Unshielded Power Inductors – SSL Series

## Electrical Characteristics

| Part Number     | Inductance<br>( $\mu$ H) | Tolerance<br>( $\pm$ %) | SRF<br>(MHz) Typ. | RDC<br>( $\Omega$ ) Max | Isat<br>(A) | Irms<br>(A) |
|-----------------|--------------------------|-------------------------|-------------------|-------------------------|-------------|-------------|
| SSL0402T-1R0M-N | 1.0                      | 20                      | 130               | 0.05                    | 2.90        | 2.9         |
| SSL0402T-1R5M-N | 1.5                      | 20                      | 115               | 0.05                    | 2.60        | 2.8         |
| SSL0402T-2R2M-N | 2.2                      | 20                      | 90                | 0.07                    | 2.30        | 2.4         |
| SSL0402T-3R3M-N | 3.3                      | 20                      | 70                | 0.08                    | 2.00        | 2.0         |
| SSL0402T-4R7M-N | 4.7                      | 20                      | 50                | 0.09                    | 1.50        | 1.5         |
| SSL0402T-5R6M-N | 5.6                      | 20                      | 47                | 0.11                    | 1.30        | 1.5         |
| SSL0402T-6R8M-N | 6.8                      | 20                      | 45                | 0.13                    | 1.20        | 1.4         |
| SSL0402T-100M-N | 10                       | 20                      | 35                | 0.16                    | 1.10        | 1.1         |
| SSL0402T-150M-N | 15                       | 20                      | 30                | 0.23                    | 0.90        | 1.2         |
| SSL0402T-220M-N | 22                       | 20                      | 20                | 0.37                    | 0.70        | 0.8         |
| SSL0402T-330M-N | 33                       | 20                      | 15                | 0.51                    | 0.58        | 0.6         |
| SSL0402T-470M-N | 47                       | 20                      | 14                | 0.64                    | 0.50        | 0.5         |
| SSL0402T-680M-N | 68                       | 20                      | 11                | 0.86                    | 0.40        | 0.4         |
| SSL0402T-101M-N | 100                      | 20                      | 9                 | 1.27                    | 0.31        | 0.3         |
| SSL0402T-151M-N | 150                      | 20                      | 6                 | 2.00                    | 0.27        | 0.25        |
| SSL0402T-221M-N | 220                      | 20                      | 5.5               | 3.11                    | 0.22        | 0.20        |
| SSL0402T-331M-N | 330                      | 20                      | 5                 | 3.80                    | 0.18        | 0.16        |
| SSL0402T-471M-N | 470                      | 20                      | 4                 | 5.06                    | 0.16        | 0.15        |
| SSL0402T-681M-N | 680                      | 20                      | 3                 | 9.20                    | 0.14        | 0.12        |
| SSL0402T-102M-N | 1000                     | 20                      | 2                 | 13.8                    | 0.10        | 0.07        |

**Note: When ordering, please specify tolerance code. Tolerance: M=±20%**

- Operating temperature range - 40°C ~ 125°C(Including self - temperature rise)
- Isat for Inductance drop 20% from its value without current
- Irms for a 30°C temperature rise from 25°C ambient with current
- Measure Equipment :

L : E4980 or HP4284A , 100kHz 0.1V

SRF : HP4291A or HP4192A

RDC : CHEN HWA 502

Isat : HP4284A+HP42841A or WK3260B+WK3265B



# SMD Unshielded Power Inductors – SSL Series

## Electrical Characteristics

| Part Number     | Inductance<br>( $\mu$ H) | Tolerance<br>( $\pm$ %) | SRF<br>(MHz) Typ. | RDC<br>( $\Omega$ ) Max | Isat<br>(A) | Irms<br>(A) |
|-----------------|--------------------------|-------------------------|-------------------|-------------------------|-------------|-------------|
| SSL0804T-1R0M-N | 1.0                      | 20                      | 100               | 0.009                   | 9.0         | 6.8         |
| SSL0804T-1R5M-N | 1.5                      | 20                      | 90                | 0.010                   | 8.0         | 6.4         |
| SSL0804T-2R2M-N | 2.2                      | 20                      | 80                | 0.012                   | 7.0         | 6.1         |
| SSL0804T-3R3M-N | 3.3                      | 20                      | 65                | 0.015                   | 6.4         | 5.4         |
| SSL0804T-4R7M-N | 4.7                      | 20                      | 45                | 0.018                   | 5.4         | 4.8         |
| SSL0804T-6R8M-N | 6.8                      | 20                      | 38                | 0.027                   | 4.6         | 4.4         |
| SSL0804T-100M-N | 10                       | 20                      | 30                | 0.038                   | 3.8         | 3.9         |
| SSL0804T-120M-N | 12                       | 20                      | 27                | 0.0432                  | 3.5         | 3.6         |
| SSL0804T-150M-N | 15                       | 20                      | 27                | 0.046                   | 3.0         | 3.1         |
| SSL0804T-220M-N | 22                       | 20                      | 19                | 0.085                   | 2.6         | 2.7         |
| SSL0804T-330M-N | 33                       | 20                      | 15                | 0.100                   | 2.0         | 2.1         |
| SSL0804T-470M-N | 47                       | 20                      | 12                | 0.140                   | 1.6         | 1.8         |
| SSL0804T-680M-N | 68                       | 20                      | 10                | 0.200                   | 1.4         | 1.5         |
| SSL0804T-101M-N | 100                      | 20                      | 9                 | 0.260                   | 1.2         | 1.3         |
| SSL0804T-151M-N | 150                      | 20                      | 6                 | 0.400                   | 1.0         | 1.0         |
| SSL0804T-221M-N | 220                      | 20                      | 5                 | 0.610                   | 0.8         | 0.8         |
| SSL0804T-331M-N | 330                      | 20                      | 4.5               | 1.020                   | 0.6         | 0.6         |
| SSL0804T-471M-N | 470                      | 20                      | 3.5               | 1.270                   | 0.5         | 0.5         |
| SSL0804T-681M-N | 680                      | 20                      | 2.5               | 2.020                   | 0.4         | 0.4         |
| SSL0804T-102M-N | 1000                     | 20                      | 2.0               | 3.000                   | 0.3         | 0.3         |
| SSL0804T-152M-N | 1500                     | 20                      | 1.4               | 4.500                   | 0.25        | 0.2         |

**Note: When ordering, please specify tolerance code. Tolerance: M=±20%**

- Operating temperature range - 40°C ~ 125°C(Including self - temperature rise)
- Isat for Inductance drop 20% from its value without current
- I rms for a 15°C temperature rise from 25°C ambient with current
- Measure Equipment :  
L : E4980 or HP4284A , 100kHz 0.1V  
SRF:HP4291A or HP4192A  
RDC : CHEN HWA 502  
Isat : HP4284A+HP42841A or WK3260B+WK3265B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without advance notice. Please contact our sales department before ordering.



# SMD Unshielded Power Inductors – SSL Series

## Electrical Characteristics

| Part Number     | Inductance<br>( $\mu$ H) | Tolerance<br>( $\pm$ %) | SRF<br>(MHz) Typ. | RDC<br>( $\Omega$ ) Max | Isat<br>(A) | Irms<br>(A) |
|-----------------|--------------------------|-------------------------|-------------------|-------------------------|-------------|-------------|
| SSL0810T-3R3M-N | 3.3                      | 20                      | 30                | 0.025                   | 10          | 4.0         |
| SSL0810T-4R7M-N | 4.7                      | 20                      | 25                | 0.033                   | 8.0         | 3.5         |
| SSL0810T-100M-N | 10                       | 20                      | 22                | 0.033                   | 8.0         | 3.5         |
| SSL0810T-150M-N | 15                       | 20                      | 18                | 0.042                   | 7.0         | 3.0         |
| SSL0810T-220M-N | 22                       | 20                      | 11                | 0.054                   | 5.5         | 2.5         |
| SSL0810T-330M-N | 33                       | 20                      | 9                 | 0.08                    | 4.0         | 2.0         |
| SSL0810T-470M-N | 47                       | 20                      | 8                 | 0.10                    | 3.8         | 1.6         |
| SSL0810T-680M-N | 68                       | 20                      | 7                 | 0.17                    | 3.0         | 1.2         |
| SSL0810T-101M-N | 100                      | 20                      | 5                 | 0.22                    | 2.5         | 1.2         |
| SSL0810T-151M-N | 150                      | 20                      | 4                 | 0.34                    | 2.0         | 0.9         |
| SSL0810T-221M-N | 220                      | 20                      | 3.5               | 0.44                    | 1.6         | 0.7         |
| SSL0810T-271M-N | 270                      | 20                      | 2.5               | 0.60                    | 1.4         | 0.6         |
| SSL0810T-331M-N | 330                      | 20                      | 2.5               | 0.70                    | 1.2         | 0.6         |
| SSL0810T-471M-N | 470                      | 20                      | 2                 | 0.95                    | 1.0         | 0.3         |
| SSL0810T-681M-N | 680                      | 20                      | 2                 | 1.2                     | 1.0         | 0.2         |
| SSL0810T-102M-N | 1000                     | 20                      | 1.5               | 2.0                     | 0.8         | 0.1         |

**Note: When ordering, please specify tolerance code. Tolerance: M=±20%**

- Operating temperature range - 40°C ~ 125°C(Including self - temperature rise)
- Isat for Inductance drop 20% from its value without current
- I rms for a 40°C temperature rise from 25°C ambient with current
- Measure Equipment :  
L : E4980 or HP4284A , 100kHz 0.1V  
SRF:HP4291A or HP4192A  
RDC : CHEN HWA 502  
Isat : HP4284A+HP42841A or WK3260B+WK3265B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without advance notice. Please contact our sales department before ordering.

# SMD Unshielded Power Inductors – SSL Series

## Electrical Characteristics

| Part Number     | Inductance<br>( $\mu$ H) | Tolerance<br>( $\pm$ %) | SRF<br>(MHz) Typ. | RDC<br>( $\Omega$ +15%) | Isat<br>(A) | Irms<br>(A) |
|-----------------|--------------------------|-------------------------|-------------------|-------------------------|-------------|-------------|
| SSL1306T-1R0M-N | 1.0                      | 20                      | 80                | 0.011                   | 20          | 8.6         |
| SSL1306T-2R2M-N | 2.2                      | 20                      | 80                | 0.014                   | 16          | 7.1         |
| SSL1306T-3R3M-N | 3.3                      | 20                      | 60                | 0.016                   | 14          | 6.2         |
| SSL1306T-4R7M-N | 4.7                      | 20                      | 45                | 0.022                   | 13          | 5.5         |
| SSL1306T-5R6M-N | 5.6                      | 20                      | 40                | 0.022                   | 12          | 5.3         |
| SSL1306T-6R8M-N | 6.8                      | 20                      | 35                | 0.022                   | 10          | 4.7         |
| SSL1306T-100M-N | 10                       | 20                      | 30                | 0.032                   | 10          | 4.3         |
| SSL1306T-150M-N | 15                       | 20                      | 22                | 0.036                   | 8.0         | 4.0         |
| SSL1306T-180M-N | 18                       | 20                      | 20                | 0.039                   | 7.5         | 3.7         |
| SSL1306T-220M-N | 22                       | 20                      | 20                | 0.047                   | 7.0         | 3.5         |
| SSL1306T-330M-N | 33                       | 20                      | 15                | 0.066                   | 5.5         | 3.0         |
| SSL1306T-470M-N | 47                       | 20                      | 9                 | 0.087                   | 4.5         | 2.6         |
| SSL1306T-680M-N | 68                       | 20                      | 8                 | 0.13                    | 3.5         | 2.3         |
| SSL1306T-101M-N | 100                      | 20                      | 7                 | 0.19                    | 3.0         | 1.8         |
| SSL1306T-151M-N | 150                      | 20                      | 6                 | 0.25                    | 2.6         | 1.5         |
| SSL1306T-221M-N | 220                      | 20                      | 5                 | 0.38                    | 2.4         | 1.2         |
| SSL1306T-331M-N | 330                      | 20                      | 4                 | 0.56                    | 1.9         | 1.0         |
| SSL1306T-471M-N | 470                      | 20                      | 3                 | 0.85                    | 1.4         | 0.82        |
| SSL1306T-681M-N | 680                      | 20                      | 2.5               | 1.2                     | 1.2         | 0.72        |
| SSL1306T-102M-N | 1000                     | 20                      | 2                 | 1.8                     | 1.0         | 0.56        |

**Note: When ordering, please specify tolerance code. Tolerance: M= $\pm$ 20%**

- Operating temperature range - 40°C ~ 125°C(Including self - temperature rise)
- Isat for Inductance drop 20% from its value without current
- I rms for a 40°C temperature rise from 25°C ambient with current
- Measure Equipment :  
L : E4980 or HP4284A , 100kHz 0.1V  
SRF:HP4291A or HP4192A  
RDC : CHEN HWA 502  
Isat : HP4284A+HP42841A or WK3260B+WK3265B

